



# Flexera® Premium Universal Adhesive

Updated September 2024

## 1. PRODUCT NAME

TEC® Flexera® Premium Universal Adhesive (774)



- Properly Prepared Gypsum
- APA Approved Plywood
- Terrazzo
- Fiber Cement Underlayment
- Radiant Heated Subfloors
- Properly Prepared VCT (Single Layer)
- Properly Prepared Sheet Vinyl (Single Layer, fully adhered)

## 2. MANUFACTURER

H.B. Fuller Construction Products Inc.  
 1105 South Frontenac Street  
 Aurora, IL 60504-6451 U.S.A.  
 800.552.6225 Office  
 800.832.9023 Technical Support  
 800.952.2368 Fax  
 tecspecialty.com

## 3. DESCRIPTION

TEC Flexera Premium Universal Adhesive is a solvent-free adhesive formulated for the installation of dimensionally stable LVT & vinyl plank without attached backing, PVC and carpet tile, VCT, quartz tile, approved bio-based tile, fiberglass-backed sheet flooring and vinyl backed resilient sheet flooring. This high strength adhesive is designed for installations over porous and non-porous substrates. TEC Flexera Premium Universal Adhesive is CRI Green Label Plus Certified, and is SCAQMD 1168 compliant.

### Key Features and Benefits

- Premium PSA offering aggressive tack and robust adhesion with very high shear and peel strength
- Long working time – Up to 12 hours
- Ultra-fast strength build – Immediate foot traffic after PSA method installation
- Heat weld after 4 hours (PSA installation)
- High moisture tolerance – Up to 99% RH & 12 lbs MVER
- Repositionable installation for dry-set
- Can install Semi-Wet Set or PSA method

### Packaging

1 gallon plastic pail (3.78 L) Product #15018427  
 4 gallon plastic pail (15.13 L) Product #15016891

### Coverage

Determine recommended trowel size based on flooring type. Coverage will vary with the absorption of substrate and trowel size. Figures below are presented only as guidelines.

Substrate/Flooring Type	Recommended Trowel Size	Approximate Coverage*
Porous substrates	1/16" x 1/16" x 1/16" (1.6 x 1.6 x 1.6 mm) Square-notch trowel	125-175 ft <sup>2</sup> /gal. <i>or</i> 14-20 yd <sup>2</sup> /gal. (12-16 m <sup>2</sup> /3.78 L)
Non-Porous substrates	1/16" x 1/32" x 1/32" (1.6 x 0.8 x 0.8 mm) U-notch trowel	175-250 ft <sup>2</sup> /gal. <i>or</i> 19-28 yd <sup>2</sup> /gal. (16-23 m <sup>2</sup> /3.78 L)
Cushion-Backed <i>or</i> Fiber Glassed-Backed Sheet Vinyl / Smooth-Backed Vinyl <i>or</i> Carpet Tile	3/8" Nap roller	250-350 ft <sup>2</sup> /gal. <i>or</i> 27-38 yd <sup>2</sup> /gal. (23-32 m <sup>2</sup> /3.78 L)

\*If recommended spread rate is exceeded, a loss of bond may occur.

### Recommended Applications

- Residential
- Light & Heavy Commercial
- Healthcare
- Institutions

### Recommended Substrates

- Concrete
- Portland Based Underlayments

### Substrate Preparation

Follow flooring manufacturer's guidelines for allowable levels of concrete moisture content. Moisture tests are recommended on concrete subfloors. Concrete substrate must be cured at least 28 days, prepared in accordance with ASTM F710, and have a maximum pH not exceeding 12. All concrete slabs must have an intact vapor barrier per ASTM E1745.

### Storage

Store at a moderate room temperature. Protect adhesive from freezing. Refer to the Technical Data section of this PDS, for more information.

### Shelf Life

Maximum of 2 years from date of manufacture in unopened container.

### Limitations

- For Interior installations only.
- Flooring must be acclimated per manufacturer's instructions.
- Do not install when the concrete RH is over 99%, per ASTM F2170.
- Do not install when MVER is over 12 lbs. per 1,000 ft<sup>2</sup> per 24 hours, per ASTM F1869.
- Although Flexera is a moisture tolerant adhesive, it does not form a moisture vapor barrier and will not protect flooring from moisture damage. Use of a moisture mitigation product such as TEC LiquidDam™ or LiquidDam EZ™ may be required for higher moisture content concrete.
- Do not install when the pH is greater than 12.
- Install only when the substrate temperature is between 50° and 90°F (10°-32°C).
- Do not install into wet adhesive over nonporous substrates.
- Do not apply over adhesive residues.
- The dimensional stability of some vinyl flooring products is very sensitive to fluctuations in ambient environment conditions. H.B. Fuller Construction Products Inc. is not responsible for installation issues caused by dimensional changes in flooring.
- It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the user's intended use.

### Cautions

Read complete cautionary information printed on product container prior to use. For medical emergency information, call 1-888-853-1758.

This Product Data Sheet has been prepared in good faith on the basis of information available at the time of publication. It is intended to provide users with information about and guidelines for the proper use and application of the covered TEC brand product(s) under normal environmental and working conditions. Because each project is different, H.B. Fuller Construction Products Inc. cannot be responsible for the consequences of variations in such conditions, or for unforeseen conditions.

## 4. TECHNICAL DATA

### Physical Properties

TEC Flexera Premium Universal Adhesive (774)	
Description	
Base Polymer	Acrylic Polymer
Color	Light Straw
Solids	57-61%
VOC Content	<1 gram per liter

## Product Data

Description	
pH	8.7
Consistency	Paste
Trowelability	Light, Easy
Shelf Life	Two years in unopened container.
Storage	40°-95°F (4°-35°C)
Application Temperature	50°-90°F (10°-32°C)
Traffic Restrictions	Foot traffic after 12 hours and heavy traffic after 24 hours for Semi-Wet Set. Light foot traffic allowed immediately after rolling, heavy traffic after 12 hours for PSA Method.
Open Time	Up to 12 hours depending on porosity and environmental conditions
Freeze/Thaw Stability	5 cycles at 20°F (-6°C)

### Composition/Information on Ingredients

**Dangerous components:** No hazardous/reportable components.

### First Aid Measures

After inhalation: Supply fresh air or oxygen; call for doctor. In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Do not induce vomiting; immediately call for medical help.

**FOR MORE INFORMATION READ SAFETY DATA SHEET**

**KEEP OUT OF REACH OF CHILDREN**

## 5. INSTALLATION INSTRUCTIONS

### Application

1. Refer to all manufacturer's recommendations and approvals prior to installation.
2. For Indoor Use Only.
3. Read Installation instructions and SDS thoroughly prior to installation.
4. For best results install at 70°F (+/- 5°) and 50% R.H. (+/-5%).
5. For proper trowel or roller selection please see Coverage section in this document.
6. Spread adhesive using the recommended trowel or roller.
  - **PSA Method** (Porous and Non-Porous Substrates). Recommended for LVP/LVT.
    - Allow spread adhesive to dry for 30-60 minutes or until adhesive is clear and does not transfer to fingertips when lightly touched.
    - Install flooring within 12 hours. Protect open adhesive from dust and debris.
  - **Semi-Wet Set Method** (Porous Substrates Only). Will result in a permanent installation and limited repositionability.
    - Allow spread adhesive to partially dry for 10-15 minutes, then install flooring.
    - Working time is approximately 20-30 minutes depending upon conditions.
7. Within 1 hour of placing flooring into the adhesive you must roll and cross roll the floor with a 100 lb. three-section roller to assure adhesive has made proper contact with the flooring.

### Clean-up

Remove wet adhesive immediately with a damp cloth. Use Mineral Spirits to remove dried adhesive. **CAUTION: Mineral Spirits are flammable. Read and follow all precautions on container label.**

## 6. AVAILABILITY

TEC premium surface preparation, tile, stone, carpet, wood and resilient floor covering installation products are available nationwide. To locate TEC products in your area, please contact:

Phone: 800-832-9002

Website: [tecspecialty.com](http://tecspecialty.com)

## 7. LIMITED WARRANTY

The product(s) covered by this Product Data Sheet are sold subject to a Limited Warranty and related terms. **H.B. Fuller Construction Products disclaims the implied warranties of merchantability and fitness for a particular purpose and all incidental and consequential damages arising out of the sale, purchase or use of this product.** For Limited Warranty details visit [tecspecialty.com](http://tecspecialty.com). To obtain a hard copy of the Limited Warranty call H.B. Fuller Construction Products at 800-832-9023 or mail a written request to the address in Section 2 of this Product Data Sheet.

## 8. MAINTENANCE

Not applicable

## 9. TECHNICAL SERVICES

### Technical and safety literature

To acquire technical and safety literature, please visit our website at [tecspecialty.com](http://tecspecialty.com).

## 10. FILING SYSTEM

Division 9



Conforms with LEED v4 low emitting interiors.  
Compliant with (CDPH) Standard Method v1.2 VOC Emissions.



To learn more, visit [TECspecialty.com](http://TECspecialty.com)



H.B. Fuller Construction Products Inc. | 1105 South Frontenac Street Aurora, IL 60504-6451



@TECInstallationSystems



tecinstallationsystems



TECInstallationSystems



TEC Installation Systems